



WONT INDUSTRIAL EQUIPMENTS

ROOM No:2,2nd FLOOR,PLOT No:200,
DAMAN WALA SERVICE COMPLEX,
GI DC ESTATE – PANDESARA[SURAT]
TELEFAX: 0261-2892847 MAIL: wontindia@ hotmail.com



Model: W-HOPT-20

Features:

- Standard epoxy powder coat finish which is resistant to chips and normal corrosion.
- Exceptionally strong but light weight steel construction, service weight is only 55kgs.
- With welded joints and reinforced fork tips for most durability in the toughest of applications.
- 3 position hand control- Raise,Lower,Neutral.
- Excellent turning angle of 190 degrees facilities.
- Number of pump strokes 12 times, lift height per stroke 11mm.
- Reliable oil leak-proof hydraulic system.
- **Conform to EN 1757-2.**
- **Option: (1)Nylon wheel, polyurethane wheel, rubber wheel,single fork roller or tandem fork rollers**
(2)Fork length:800mm,900mm,1000mm,1100mm.

Main specifications:

Model		W-HOPT
Capacity	Q(kg)	2000
Lowered fork height	h13(mm)	75
Steering wheel	mm	φ160
Fork wheel single	mm	φ70x80
Fork wheel tandem	mm	φ70x60
Max. lift height	h3(mm)	190
Total height	h14(mm)	1160
Overall length	l1(mm)	1520
Fork length	l(mm)	1150
Width overall forks	b5(mm)	520
Ground clearance,centre of wheelbase	m2(mm)	22
Aisle width for pallets 1000x1200 crossways	Ast(mm)	1720
Aisle width for pallets 800x1200 lengthways	Ast(mm)	1770
Turning radius	Wa(mm)	1265
Service weight	kg	55-60

Remark: Special size for width and length can be made according to customer's requirement.