



WONT INDUSTRIAL EQUIPMENTS

ROOM No:2,2nd FLOOR,PLOT No:200,
DAMAN WALA SERVICE COMPLEX,
GI DC ESTATE – PANDESARA[SURAT]

TELEFAX: 0261-2892847 MAIL: wontindia@ hotmail.com

BATTERY PLATFORM TRUCK

Capacity : 2000 & 3000 kg.

SALIENT FEATURES

- Easy to Operate.
- Robust in Construction.
- Excellent Manoeuverability.
- Compact and Economical Design.
- Reliable Electrical Circuit.
- Easy Access to All Components.

TRAVELING SPEEDS (KM/HR)

- For 2000 kg Laden 7 - 9, Unladen 9 - 11
- For 3000 kg Laden 5 - 7, Unladen 7 - 9
- Drive Unit : Series wound traction motor is mounted above the drive wheel. Motor is connected to drive wheel by 3 stage reduction gear box.
- Steering : Effortless steering under heavy load is achieved by using heavy duty self aligned ball bearings & thrust bearings.
- Brakes : The brake consist of two internal expanding shoes mounted on rear axel with parking brake facility.
- Controls : Dash board consists of controls for key switch, forward, reverse motion selector switch, horn, light and emergency cut off push button. Accelerator and brake paddle are foot operated.
- Electronic Controls : Electronic controls for soft start and jerk free transmission gives better battery life & lower maintenance cost.

